



平板燈型號	SED6060PL40W (2*2)	藍芽手機調光控制 Android4.3/iOS6 以上版本	SED12060PL60W (4*2)	SED12030PL40W (4*1)
認證	台灣 BSMI	台灣 BSMI	台灣 BSMI	台灣 BSMI
光生物安全檢驗 (CNS15592)	PASS	PASS	PASS	PASS
連接方式	燈體出線接AC, 電源外置	燈體出線接AC, 電源外置	燈體出線接AC, 電源外置	燈體出線接AC, 電源外置
工作電壓	AC100~240V,50/60Hz	AC100~240V,50/60Hz	AC100~240V,50/60Hz	AC100~240V,50/60Hz
輸入功率	40W (相當於T8 2呎 * 4支20W燈管)	40W (相當於T8 2呎 * 4支20W燈管)	60W (相當於T8 4呎 * 3支40W燈管)	40W (相當於T8 4呎 * 2支40W燈管)
PF值	≥0.95	≥0.95	≥0.9	≥0.9
色溫	3000K/4000K/5700K/6500K	3000K/4000K/5700K/6500K	3000K/4000K/5700K/6500K	3000K/4000K/5700K/6500K
光通量(LM)	2880/2980/3500/3500	手機調光 0 ~ 3500	5300/5300/5500/5500	2880/2980/3200/3200
演色性 (CRI)	≥80	≥80	≥80	≥80
R9	>0	>0	>0	>0
LED顯示是否頻閃	無	無	無	無
壽命	30,000Hr	30,000Hr	30,000Hr	30,000Hr
照明角度	120°	120°	120°	120°
使用環境溫度	-20°C ~ +40°C	-20°C ~ +40°C	-20°C ~ +40°C	-20°C ~ +40°C
產品尺寸 (mm)	600*600*12	600*600*12	1200x600x12	1200x300x12
手機APP QR Code		   		